



Engine		TT3.35	TT3.50
Net advertised power		36	50
Displacement	(L)	2.4	2.7
Max. torque @ 1400 +/- erpm	(Nm)	142 @ 1400 +/- 100	180 @ 1300 +/- 100
Transmission & Clutch			
8x8 Mechanical Synchro Shuttle transmission		•	•
Minimum speed / Maximum road speed	(kph)	2.54/28.16	3.0/33.24
Front Axles			
4WD front axle		•	•
Turning radius 4WD Portal	(M)	2.9	2.9
Linkage			
Category		1-11	1-11
Lift capacity @ ball ends (Std)	(kg)	1800	1800
РТО			
Rear PTO	(Std)	540	540
GSPTO (Ground speed PTO)	(Std)	•	•
Rear PTO engine speed at 540	(rpm)	2016	2016
Operator environment			
Mechanical suspension seat with seat belt on inclined plane		•	•
Semi Flat deck operator area		•	•
Tyres			
Front 8.0x18 Ag		•	•
Dimensions			
Wheelbase	(mm)	1990	1990
Overall width	(mm)	1690	1700
Height to top of ROPS	(mm)	2460	2442
Ground Clearance under Front axle	(mm)	355	355
Weight (Standard Ballast)	(kg)	2025	2025





To be successful in your business you need your machines to be powerful, easy to use and capable of performing at their best in the toughest conditions.

Luzon : 0917-6349473 Visayas : 0917-6331734 Mindanao : 0917-6331720



Only genuine parts are made for your machine and designed for peak performance. We engineer, manufacture, and choose parts based on the strictest design and testing standards.

Luzon : 0917-6331795 Visayas : 0917-8061789 Mindanao : 0917-3296244



We strive to ensure that the latest ideas from the industry continue to be of relevance even after your machine has been delivered.

We are committed to minimize costs and the length of your idle time.

Luzon : 0917-3106399 Visayas : 0917-8327159 Mindanao : 0917-3128049



